

## GuideLed 11611, 11621, 11625 AT

- LED self contained luminaire with automatic test for reduced inspection effort
- Universal use for maintained and non-maintained operation and for 1 h, 2 h or 3 h operation
- Including pictogram kit (arrow down, left, right) acc. to ISO 7010
- Environmentally-friendly due to modern lithium ion technology
- Low operating costs via low connected load
- Minimum maintenance effort and increased safety via use of 3-chip LEDs with high service life (50,000 hours)
- Optimal recognition via bright pictogram with high uniformity  $L_{min}/L_{max} > 0.6$
- Photometric data according to EN 1838 and ISO 30061
- Simple fault analysis and status display via bicolor LED and testing button
- 1 minute switch-back delay after mains return (according to DIN VDE 0100-718)

GuideLed 11611 AT



GuideLed 11621 AT



GuideLed 11625 AT




Viewing distance	30 m
Luminous flux $\Phi_e / \Phi_{norm}$ at end of rated operating time	95 % at 1 h; 95 % at 2 h; 90 % at 3 h 85 % at 1 h; 80 % at 2 h; 60 % at 3 h
Housing material	Polycarbonate
Weight	0.77 kg (11611 AT) 1.04 kg (11621 AT) 1.06 kg (11625 AT)
Housing colour	Light grey RAL 7035
Type of mounting	Insulation class II (protective earth required)
Terminals	Through-wiring from mains (L, L', N, PE) to 2.5 mm <sup>2</sup>
Connection voltage	220- 240 V, 50 Hz
Power consumption mains operation (apparent power/effective power)	4.0 VA / 3.6 W 11611 4.5 VA / 4.2 W 11621/11625
Permissible ambient temperature	Maintained mode -5 °C to +30 °C Non-maintained mode 0 °C to +35 °C
Battery	Lithium ion 3.7 V/2000 mAh with multiple protective circuit
Light source	LED strip with 3-chip LEDs


## Ordering details

Type	Scope of supply	Order No
GuideLed 11611 AT	GuideLed 11611 1-3h/D AT-Set-e for wall mounting, including LED-supply and pictogram kit (LED pictogram + ISO arrow down, left, right), 30 m	40071353572
GuideLed 11621 AT	GuideLed 11621 1-3h/D AT-Set-e for ceiling mounting, including LED-supply and pictogram kit (LED pictogram + ISO arrow down, left, right + blind), 30 m	40071353578
GuideLed 11625 AT	GuideLed 11625 1-3h/D AT-Set-e for rope suspension, including LED-supply and pictogram kit (LED pictogram + ISO arrow down, left, right + blind), 30 m	40071353579


GuideLed 11611 AT



GuideLed 11621 AT



GuideLed 11625 AT



Dimensions in mm